

- DEVELOPER'S SURVEYOR SHALL SET A LATH AT THE INTERSECTION OF THE PROPERTY LINE AND THE PUBLIC UTILITY EASEMENT. DEVELOPER'S SURVEYOR SHALL ALSO MARK THE PROPERTY LINE AND LOT NUMBERS ON THE FACE OF CURB WITH WHITE PAINT.
- 2. IF PROPERTY CORNER MONUMENTS HAVE NOT BEEN SET AT THE TIME OF WATER SERVICE INSTALLATION, THE DEVELOPER'S SURVEYOR SHALL SET A LATH AT THE PROPERTY CORNER LOCATION ON THE RIGHT-OF-WAY LINE.
- 3. ORS 92.044(7) PROHIBITS LOCATING ANY UTILITY INFRASTRUCTURE WITHIN 1-FT OF A SURVEY MONUMENT. DEVELOPER SHALL PAY FOR ANY RELOCATION OF SERVICES AND/OR METER BOXES FOUND TO FALL WITHIN 1-FT OF A SURVEY MONUMENT LOCATION.
- METERS SHALL ONLY BE INSTALLED IN SIDEWALK IF APPROVED BY DISTRICT ENGINEER. SHOWN IN SIDEWALK FOR INFORMATION ONLY. BOXES SHALL BE INSPECTED BY DISTRICT PRIOR TO POURING CONCRETE SIDEWALK.
- 5. SEE SECTION 8.2. OF THE STANDARDS FOR BACKFLOW REQUIREMENTS.



DESIGNED: MBA APPROVED: NWA

SCALE: NONE

SINGLE WATER SERVICE TYPICAL INSTALLATION WITH CURBTIGHT SIDEWALK

DATE: 9/2020

**DETAIL** 

601